


NGB Series

NON GROUND BEARING



TRIPLE AXLE MODELS: NGB 50 AND NGB 60



STANDARD SERIES FEATURES

- 22' loadwell with 24 12" outriggers, 2" lumber decking & 3 "D" lashing rings
- 5" axles; 16-1/2" x 7" air brakes; unimount 10 stud
- High capacity spring suspension
- Self-contained hydraulic system w/electric start engine
- Visible 4 position ride adjustment with 2" increments
- 50 Ton - Twin 6" hydraulic cylinders
- 60 Ton - Twin 8" hydraulic cylinders
- Hydraulic operated neck support
- Air actuated safety lock
- Rubber-mounted lights
- Finished with industrial enamel over prime coat; color of your choice from our standard color selection
- Scraper neck and tapered front beam

SEE OPTIONS SECTION FOR AVAILABLE OPTIONS

Model	Capacity	Noof Axles	Deck Length	LOA
NGB 50	100,000#	3 each	22'	48'-6"
NGB 60	120,000#	3 each	22'	48'-6"

NOTES:



Rugged Durability, Performance, Value.

6101 South McIntosh Road, Sarasota, Florida 34238 • For additional information or your Witzco Challenger dealer nearest you, Call: (941) 922-5301 • Toll Free: 1-888-922-9900 • Fax: (941) 924-2402 • E-mail: info@witzco.com • Website: www.witzco.com

Model: NGB 50

NON GROUND BEARING



GENERAL DATA SHEET - PART NUMBER NGB 50

Model: NGB 50 Non Ground Bearing Hydraulic Detachable Gooseneck Trailer

Capacity: 100,000#

Trailer weight: 19,920# +/- 3%

Gross vehicle weight rating: 119,920#

DIMENSIONS:

- Overall Length: 48' 2"
- Overall Width: 8' 6"
- Loadwell length: 22'
- Loadwell height: 25" unloaded

GOOSENECK STYLE & DIMENSIONS:

- Style: 2 angle scraper NON GROUND BEARING
- Length: 11' 3"
- 5th wheel height: 50"
- Swing clearance: 90"
- Kingpin setting: 15"
- Kingpin size: 2"

HYDRAULIC SYSTEM:

- Engine: 10 HP electric start
- Pump: 2 GPM
- Control valve: 2500 psi
- Cylinder: (2) 6" bore w/22" stroke

BED STRUCTURE W/TAPERED FRONT BEAM:

- Main frame: W16x77 beams A992 grade 50
- Side Beam: W 12x22 A992 grade 50
- Cross members: W8x10 A992 full width
- Decking: 2" Oak lumber
- 12" cast iron outriggers, 12 each side

SUSPENSION:

- Hutch #H9700TUS-49AC-UN/MT Spring and equalizer, #365-00 heavy duty 3 leaf spring

AXLES:

- 3 Hendrickson 5" round 25,000# capacity w/Hub piloted wheels

RIMS & TIRES:

- Unimount style 8.25" x 22.5"
- 255/70 R 22.5 Radial Tires

BRAKE SYSTEM:

- 16-1/2" x 7" air S cam w/automatic slack adjusters
- Type 30 and Type 30/30 brake chambers

LIGHT SYSTEM:

- Sealed modular wire harness
- 12-volt rubber mounted seal beam lights
- Reflective tape

LASHING "D" RINGS:

- 3 per side of deck
- 1 on trunion between tires

FINISH:

- 1 coat rust inhibitive enamel primer
- 2 coats high performance water bourne one part urethane
- Choice of 7 factory standard colors

Model: NGB 60

NON GROUND BEARING



GENERAL DATA SHEET - PART NUMBER NGB 60

Model: NGB 60 Non Ground Bearing Hydraulic Detachable Gooseneck Trailer

Capacity: 120,000#

Trailer weight: 23,340# +/- 3%

Gross vehicle weight rating: 143,340#

DIMENSIONS:

- Overall Length: 48' 6"
- Overall Width: 8' 6"
- Loadwell length: 22'
- Loadwell height: 25" unloaded

GOOSENECK STYLE & DIMENSIONS:

- Style: 2 angle scraper NON GROUND BEARING
- Length: 11' 6"
- 5th wheel height: 50"
- Swing clearance: 90"
- Kingpin setting: 15"
- Kingpin size: 2"

HYDRAULIC SYSTEM:

- Engine: 10 HP electric start
- Pump: 2 GPM
- Control valve: 2500 psi
- Cylinder: (2) 8" bore w/22" stroke

BED STRUCTURE W/TAPERED FRONT BEAM:

- Main frame: W16x100 beams A992 grade 50
- Side Beam: W12x22 A992 grade 50
- Cross members: W8x10 A992 full width
- Decking: 2" Oak lumber
- 12" cast iron outriggers, 12 each side

SUSPENSION:

- Hutch #H9700TUS-49AC-UN/MT Spring and equalizer, #365-00 heavy duty 3 leaf spring

AXLES:

- 3 Hendrickson 5" round 25,000# capacity w/Hub piloted wheels

RIMS & TIRES:

- Unimount style 8.25" x 22.5"
- 255/70 R 22.5 Radial Tires

BRAKE SYSTEM:

- 16-1/2" x 7" air S cam w/automatic slack adjusters
- Type 30 and Type 30/30 brake chambers

LIGHT SYSTEM:

- Sealed modular wire harness
- 12-volt rubber mounted seal beam lights
- Reflective tape

LASHING "D" RINGS:

- 3 per side of deck
- 1 on trunion between tires

FINISH:

- 1 coat rust inhibitive enamel primer
- 2 coats high performance water borne one part urethane
- Choice of 7 factory standard colors